



Portable Cut-off
DLW140 355 mm (14")



World's First Cordless Portable Cut-off

(as of October 1, 2018)



Cutting work
Amount

130cuts

75 x 45mm, T : 0.8mm metal stud
with BL1850B x 2

18v + 18v → 36v



18v + 18v → 36v



Toolless replacement of abrasive cut-off wheel



BL MOTOR

Load status indicator



As the motor load increases, the lighting lamp increases.

Electric brake

Quick release vise



Carry handle
for easy transport to job site



Toolless adjustment of guide plate



allows for easy adjustment of the guide plate by simple handling

- 3 stage position change
- 0 to 45 degree angle adjustment

Large spark guard



Saw head locking by pin lock



makes it easy to lock down the saw head for storage and transport.

■ Cutting Capacity

A workpiece thinner than 1.6 mm is recommended for cutting with this tool.

Form of materials	Miter angle	
	0°	45°
	D : $\phi 127\text{mm}$ (5")	D : $\phi 127\text{mm}$ (5")
	H x W : 115 x 130 (4-1/2"x5-1/8") 102 x 194mm (4"x 7-5/8") 70 x 233mm (2-3/4"x 9-1/8")	H x W : 115 x 103mm (4-1/2"x 4-1/16")
	H x W : 119 x 119mm (4-11/16"x 4-11/16")	H x W : 106 x 106mm (4-3/16"x 4-3/16")
	S x S : 137 x 137mm (5-3/8"x 5-3/8")	S x S : 100 x 100mm (4"x 4")

D : Diameter W : Width H : Height S : Side

■ Accessory

Abrasive cut-off wheel

For all ferrous materials (Steel, cast iron) and other hard metals.

Size (mm) : 355x2.5x25.4
Grit : A36P-BF

Part No. B-64711



Portable Cut-off

DLW140 355 mm (14")

- Brake
- Soft Start

Wheel Diameter	355 mm (14")
Hole Diameter	25.4 mm (1")
No Load Speed (RPM)	3,800
Max Output	1,300 W
Vibration Level	2.5 m/s ²
Sound Pressure Level	103 dB
Sound Power Level	115dB
Dimensions (L x W x H)	537x290x640 mm (21-1/8"x11-3/8"x25-1/4")
Net weight	17.2 - 17.8 kg (37.9 - 39.3 lbs.)

Standard Equipment : Abrasive Cut-Off Wheel

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.



Bonded Abrasive Accessories

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201810