

Easy-to-Customize

Standardized intervals between base plate setting screws enable to use various Base plates for a wide range of applications.

Plunge base assembly
with Side grip

Router Setup



Grip (option)
Part No. 153489-2

Convenient for cutting while applying weight on one of the two handles of the base



Convenient Tool Bag

Square-shaped tool bag with standardized size of inner tray enables to put various items into the bag such as Guide rail adapter set, Router bit set, Motor unit, Base assemblies, etc.



Tool not supplied with adapter set and bit sets



RT0700CX2		6.35mm	411
	Double Insulation		
	Variable Speed		
	Constant Speed		
	Soft Start		
	Dust Collecting		
Continuous rating Input 710W			
Capacity Collet: 6.35mm			
No load speed (r/min) 10,000-30,000			
Dimensions (L x W x H) 89x89x200mm			
Net Weight* 1.8kg			
Power supply cord 2.5m			
Tool supplied with trimmer base, tilt base, plunge base and straight guide in a carry bag.			

*weight according to EPTA-Procedure 01/2003

NEW

Satisfy Professional's Needs

Makita

RT0700CX2

ULTIMATE MINI ROUTER

3 Different Base Assemblies
for Added Versatility



**COMES WITH
TOOL BAG**

Available in various combinations for added versatility



with Trimmer base

Round base assembly for smooth and fast cutting with easy handling



Enlarged opening section of base assembly for excellent bit visibility while maintaining durability.



Precision cutting depth adjustment

- Non-slip elastomer-covered body grip for increased operator comfort.
- Simple and efficient base lock system
- High durability and accuracy obtained by using aluminum for trimmer base
- Replaceable, non-marring plastic base plate for protection of trimmer base and smooth sliding on work surface



High power, durable and accurate Trimmer.

Shaft lock, Flat-top design and Horizontally installed power supply cord provides stability for easier bit change.



Variable speed control by dial



- Accepts 6.35mm collets
- High durability and accuracy obtained by using aluminum for body housing

with Tilt base

Ergonomic body grip easy-to-grasp with one hand
Tilting capacity: -30° to 45°



Enlarged opening section of base assembly for excellent bit visibility.



Precision cutting depth adjustment

- Non-slip elastomer-covered body grip for increased operator comfort.
- Simple and efficient base lock system
- High durability and accuracy obtained by using aluminum for base holder
- Replaceable, non-marring plastic base protector for protection of base plate and smooth sliding on work surface



with Plunge base

Precision cutting depth adjustment
Plunge capacity: 0 - 35mm



Ergonomically contoured knob style handles



Optional Fine adjusting straight guide can be used.

- Easy-to-operate lock lever
- Rubberized soft grip
- 3 stage cut depth adjustment
- High durability and accuracy obtained by using aluminum for plunge base
- Replaceable, non-marring plastic base plate for protection of plunge base and smooth sliding on work surface



High Power
710W