



2023 / 2024 CATALOGUE



Affordable • Reliable • Repairable

Angle Grinder.....	4
Belt Sander	4
Blower	6
Circular Saw	5
Drill	3
Jig Saw	5
Finishing Sander.....	4
High Speed Drill.....	2
Impact Drill	3
Portable Cut-Off Saw.....	5
Horizontal Handle Cut-Off Saw	5
Power Planer.....	5
Random Orbit Sander.....	4
Recipro Saw.....	5
Rotary Drill	2
Rotary Hammer	3
Router	6
Trimmer.....	6

M0801B.....	3
M0921B.....	4
M1901B.....	5
M1902B.....	5
M2401B.....	5
M2402B.....	5
M3600B.....	6
M3601B.....	6
M3700B.....	6
M4000B.....	6
M4301B.....	5
M4501KB.....	5
M5802B.....	5
M6001B.....	2
M6002B.....	2
M6201B.....	2
M6501B.....	2
M8100B.....	3
M8101B.....	3
M8700B.....	3
M8701B.....	3
M9002B.....	4
M9200B.....	4
M9203B.....	4
M9204B.....	4
M9400B.....	4
M9507B.....	4

Note

- Makita reserves the right to change specifications of parts and accessories without notice.
- Items of standard equipment and specifications may vary by country or area.
- Actual product color may differ slightly from color reproduced here.
- Weight data in this catalogue is the value measured by us according to EPTA Procedure 01/ver.2.1.

M6501B High Speed Drill 6.5mm

85

Compact body for superior handling



Continuous rating input	230W
Capacity	Steel: 6.5mm Wood: 9mm
No Load Speed (r/min)	0 - 4,500
Dimensions (L x W x H)	203x63x171mm
Net weight	0.95kg
Power supply cord	2.0m



Geared Chuck
Chuck Key

M6001B Rotary Drill 10mm

85

Compact and lightweight, yet with enough power.



Continuous rating input	450W
Capacity	Steel: 10mm Wood: 25mm
No Load Speed (r/min)	0 - 3,000
Dimensions (L x W x H)	229x64x175mm
Net weight	1.3kg
Power supply cord	2.0m



Geared Chuck
Chuck Key

M6002B Rotary Drill 10mm

85

Powerful motor with 450W input power.



Continuous rating input	450W
Capacity	Steel: 10mm Wood: 25mm
No Load Speed (r/min)	0 - 3,000
Dimensions (L x W x H)	234x64x175mm
Net weight	1.3kg
Power supply cord	2.0m



Keyless Chuck

M6201B Rotary Drill 13mm

303

With Rotation reversing facility.



Continuous rating input	750W
Capacity	Steel: 13mm Wood: 36mm
No Load Speed (r/min)	600
Dimensions (L x W x H)	267x86x396mm
Net weight	2.7kg
Power supply cord	2.0m



Geared Chuck
Chuck Key, Depth Gauge, Side Grip 36 complete

IMPACT DRILLING

M0801B Impact Drill 13mm

85

Variable speed control by trigger from 0 to 3,200 min⁻¹.



Continuous rating input	500W
Capacity	Concrete: 16mm Steel: 13mm Wood: 20mm
Impacts Per Minute (i/min)	48,000
No Load Speed (r/min)	3,200
Dimensions (L x W x H)	262x70x196mm
Net weight	1.7kg
Power supply cord	2.0m

Geared Chuck
Chuck Key, Side Grip



M8100B Impact Drill 13mm

85

Tool body ergonomically designed to give maximum power thrust.



Continuous rating input	710W
Capacity	Concrete: 16mm Steel: 13mm Wood: 30mm
Impacts Per Minute (i/min)	0-48,000
No Load Speed (r/min)	0-3,200
Dimensions (L x W x H)	296x77x202mm
Net weight	2.1kg
Power supply cord	2.0m

Geared Chuck
Depth Gauge, Side Grip, Chuck Key



M8101B Impact Drill 13mm

85

Tool body ergonomically designed to give maximum power thrust.



Continuous rating input	710W
Capacity	Concrete: 16mm Steel: 13mm Wood: 30mm
Impacts Per Minute (i/min)	0-48,000
No Load Speed (r/min)	0-3,200
Dimensions (L x W x H)	295x77x202mm
Net weight	2.0kg
Power supply cord	2.0m

Keyless Chuck
Depth Gauge, Side Grip



M8700B Rotary Hammer 22mm

459

Adapted for SDS-PLUS bits

1.9J Combination Hammer, SDS-Plus



Continuous rating input	710W
Capacity	Concrete: 22mm Steel: 13mm Wood: 32mm
Impacts Per Minute (i/min)	0-4,350
No Load Speed (r/min)	0-1,100
Dimensions (L x W x H)	362x71x194mm
Net weight	2.5kg
Power supply cord	5.0m

Depth Gauge, Side Grip
Tool does not come with bit.



M8701B Rotary Hammer 26mm

459

Adapted for SDS-PLUS bits

2.3 J Combination Hammer, SDS- PLUS bits.



Continuous rating input	800W
Capacity	Concrete: 26mm Steel: 13mm Wood: 32mm
Impacts Per Minute (i/min)	0-4,500
No Load Speed (r/min)	0-1,200
Dimensions (L x W x H)	362x71x194mm
Net weight	2.7 - 3.1kg
Power supply cord	4.0m

Depth Gauge, Side Grip
Tool does not come with bit.



GRINDING & SANDING

M9507B Angle Grinder 115mm

459

Compact yet powerful.



Continuous rating input	720W
Wheel diameter	115mm
No Load Speed (r/min)	11,000
Dimensions (L x W x H)	261 x 130 x 111 mm
Net weight	1.9kg
Power supply cord	2.0m



Side Grip, Lock Nut Wrench
Tool does not come with depressed center wheel.

M9002B Angle Grinder 125mm

303 or 304

Industrial performance and durability at less expense.



Continuous rating input	1,050W
Wheel diameter	125mm
No Load Speed (r/min)	11,000
Dimensions (L x W x H)	361 x 140 x 124 mm
Net weight	2.8kg
Power supply cord	2.0m



Lock Nut Wrench, Side Grip
Tool does not come with depressed center wheel.

M0921B Angle Grinder 230mm

203

Heavy-duty motor. High performance.



Continuous rating input	2,200W
Wheel diameter	230mm
No Load Speed (r/min)	6,600
Dimensions (L x W x H)	439 x 250 x 141 mm
Net weight	5.3kg
Power supply cord	2.0m



Lock Nut Wrench, Side Grip
Tool does not come with depressed center wheel.

M9400B Belt Sander 100mm

153 or 155

Industrial performance and durability.



Continuous rating input	940W
Belt size	100 x 610mm
Belt speed	380m / min.
Dimensions (L x W x H)	354 x 175 x 169 mm
Net weight	6.2kg
Power supply cord	2.0m



Abrasive belt, Step, Dust bag assembly, Carbon plate

M9200B Finishing Sander

419

1/4 Sheet 180W Finishing Sander. Extremely versatile.



Continuous rating input	180W
Pad Size	112 x 102mm
Abrasive Paper Size	114 x 140mm
Orbits Per Minute (o/min)	14,000
Dimensions (L x W x H)	110 x 112 x 133 mm
Net weight	0.9kg
Power supply cord	2.0m



Abrasive paper x6

M9203B Finishing Sander

63 or 64

1/3 Sheet 190W Finishing Sander with Built-in Dust Extraction System



Continuous rating input	190W
Pad Size	92 x 185mm
Abrasive Paper Size	93 x 228mm
Orbits Per Minute (o/min)	12,000
Strokes Per Minute (s/min)	24,000
Orbit Diameter	2.0mm
Vibration Level	Sanding metal plate: 5.0 m/s ²
Vibration K factor	1.5 m/s ²
Sound Pressure Level	75 dB(A)
Noise K factor	3 dB(A)
Dimensions (L x W x H)	252 x 92 x 154 mm
Net weight	1.4kg
Power supply cord	2.0m



Abrasive Paper, Punch Plate, Dust Bag

M9204B Random Orbit Sander

419

240W Random Orbit Sander With Built-in Dust Extraction System



Continuous rating input	240W
Pad Size	123mm
Abrasive Paper Size	125mm
Orbits Per Minute (o/min)	12,000
Strokes Per Minute (s/min)	24,000
Orbit Diameter	2.8mm
Vibration Level	Sanding metal plate: 3.0 m/s ²
Vibration K factor	1.5 m/s ²
Sound Pressure Level	81 dB(A)
Sound Power Level	92 dB(A)
Noise K factor	3 dB(A)
Dimensions (L x W x H)	153 x 123 x 144 mm
Net weight	1.2kg
Power supply cord	2.0m



Dust Bag, Abrasive Paper



SAWING



M2401B Portable Cut-Off Saw 355mm 203

2,000W Cut-Off Saw



Continuous rating input	2,000W
Wheel diameter	355mm
No Load Speed (r/min)	3,800
Capacity at 90°	Round: 127mm Rectangular: 102x194mm Rectangular: 70x233mm
Capacity at 45°	Round: 127mm Rectangular: 155x103mm
Dimensions (L x W x H)	500x280x620mm
Net weight	13.7kg
Power supply cord	2.5m

Abrasive Cut-Off Wheel, Hex Wrench

M2402B Horizontal Handle Cut-Off Saw 355mm 203

2,200W



Continuous rating input	2,200W
Wheel Diameter	355mm
No Load Speed (r/min)	3,900
Capacity at 90°	Round: 127mm Rectangular: 102x194mm Rectangular: 70x233mm
Capacity at 45°	Round: 127mm Rectangular: 155x103mm
Dimensions (L x W x H)	500x280x630mm
Net weight	14.0 - 15.5kg
Power supply cord	2.5m

Abrasive Cut-Off Wheel, Hex Wrench

M4301B Jig Saw 63 or 64

450W Top Handle Jig Saw - 3 Orbital Settings Plus Straight Cutting



Continuous rating input	450W
Max Cutting Capacity at 90°	Wood: 65mm Steel: 6mm
Length of Stroke	18mm
Strokes Per Minute (s/min)	0 - 3,100
Vibration Level	Cutting Wood: 8.0 m/s ²
Vibration K factor	Cutting Wood: 1.5 m/s ²
Vibration Level	Cutting Sheet Metal: 5.0 m/s ²
Vibration K factor	Cutting Sheet Metal: 1.5 m/s ²
Sound Pressure Level	82 dB(A)
Sound Power Level	93 dB(A)
Noise K factor	3 dB(A)
Dimensions (L x W x H)	214x75x202mm
Net weight	1.9kg
Power supply cord	2.0m

Jig Saw Blade, Hex Wrench

M4501KB Recipro Saw 303 or 304

Toolless blade damp



Continuous rating input	1,010W
Length of Stroke	28mm
Strokes Per Minute (s/min)	0 - 2,800
Capacity	Pipe: 130mm Wood: 255mm
Vibration Level	Cutting Boards: 19.5 m/s ²
Vibration K factor	Cutting Boards: 1.5 m/s ²
Vibration Level	Cutting Wooden beams: 22.0 m/s ²
Vibration K factor	Cutting Wooden beams: 2.0 m/s ²
Sound Pressure Level	87 dB(A)
Sound Power Level	98 dB(A)
Noise K factor	3 dB(A)
Dimensions (L x W x H)	457x98x170mm
Net weight	3.2kg
Power supply cord	2.0m

2 x Reciprocating Saw Blades

M5802B Circular Saw 303 or 304

190mm / 185mm 1,050W



Continuous rating input	1,050W
Blade Diameter	190 / 185mm
Max Cutting Capacity	at 90°: 68/66mm at 45°: 46/44mm
No Load Speed (r/min)	4,900
Vibration Level	Cutting Wood: 2.5 m/s ² or less
Vibration K factor	Cutting Wood: 1.5 m/s ²
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Noise K factor	3 dB(A)
Overall Length	297mm
Net weight	4.0kg
Power supply cord	2.0m



Dust nozzle: (Optional)
TCT Saw Blade, Guide Rule, Hex Wrench



Planing / Routering

M1901B Power Planer 82mm 410 or 411



Continuous rating input	500W
Planing Width	82mm
Planing Diameter	2mm
Shiplapping	9mm
No Load Speed (r/min)	16,000
Vibration Level	Planing Softwood: 3.5 m/s ²
Vibration K factor	Planing Softwood: 1.5 m/s ²
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Noise K factor	3 dB(A)
Overall Length	285mm
Net weight	2.7kg
Power supply cord	2.0m

Planer Blade, Blade gauge assembly, Socket wrench

M1902B Power Planer 82mm 410 or 411

Power planer with excellent cost performance



Continuous rating input	500W
Planing Width	82mm
Planing Depth	1mm
No Load Speed (r/min)	16,000
Diameter (L x W x H)	285x157x160mm
Net weight	2.7kg
Power supply cord	2.0m

Planer blade 82, Blade gauge assembly, Socket wrench 9
Rebate: 9mm

M3601B Router 6.35mm

106 or 113

6mm, 8mm Plunge Router



Continuous rating input	900W
Collet Capacity	6.35mm
Plunge Capacity	0-35mm
No Load Speed (r/min)	27,000
Vibration Level	Cutting Grooves in MDF: 7.5 m/s ²
Vibration K factor	Cutting Grooves in MDF: 1.5 m/s ²
Sound Pressure Level	91 dB(A)
Sound Power Level	102 dB(A)
Noise K factor	3 dB(A)
Overall Length	256mm
Net weight	2.7kg
Power supply cord	2.0m



Straight Guide, Straight Bit, Collet Cone, Wrench

M3600B Router 12.7mm

203 or 204

Heavy duty 12.7mm Plunge Router



Continuous rating input	1,650W
Collet Capacity	12.7mm
Plunge Capacity	0-60mm
Base dia.	160x148mm
No Load Speed (r/min)	22,000
Diameter (L x W x H)	284x148x300mm
Net weight	5.5kg
Power supply cord	2.0m



Straight Guide, Guide holder assembly, Collet sleeve x2, Straight Bit, Wrench, Template guide, Trimmer guide assembly



TRIMMER

M3700B Trimmer 6.35mm

410 or 411

Transparent plastic base: Excellent bit visibility, Lightweight, High maneuverability



Continuous rating input	530W
Collet Capacity	6.35mm
Plunge Capacity	0-42mm
No Load Speed (r/min)	35,000
Diameter (L x W x H)	82x90x199mm
Net weight	1.4kg
Power supply cord	2.0m



Trimmer guide assembly, Straight guide assembly, Template guide, Straight bit, Wrench x2, Chip detector

BLOWER

M4000B BLOWER

85

In-line and ergonomically designed grip for easily applying the nozzle to the target to be blown away



Continuous rating input	530W
Air volume	1.2 - 2.9m ³ /min
No Load Speed (r/min)	8,500-16,000
Diameter (L x W x H)	427x161x212mm
Net weight	1.5kg
Power supply cord	2.0m



Nozzle assembly



Makita[®]
mt



Image: M3700B


















Makita®

mt

Affordable • Reliable • Repairable

STANDARD DUTY INDUSTRIAL POWER TOOLS

ICON

- | | | | |
|---|--|---|---|
|  Double Insulation |  Keyless Chuck |  Hook & Loop |  Orbital Cutting |
|  Variable Speed |  Mechanical 2-Speed |  Torque Limiter |  Bayonet Shank Jig Saw Blade |
|  Brake |  Soft Start |  Bevel Cutting |  Carrying Case |
|  Reversing |  Dust Collecting |  Bevel Cutting 45 LR | |
|  Mechanical 2-Speed |  SDS-PLUS Shank | | |

Rutherford
a member of the *Hudaco* group

DEALER STAMP

FOR WHOLESALE TRADE ENQUIRIES ONLY

CAPE TOWN
TEL: (021) 932-0568

DURBAN
TEL: (031) 717-6400

JOHANNESBURG
TEL: (011) 878-2600

www.makita.co.za

 Like us on
Facebook
<http://facebook.com/MakitaPowerToolsSA>

GUARANTEE: These machines have been thoroughly inspected and tested before leaving the factory and are guaranteed against defective workmanship and materials. Should any problems develop the complete machine must be returned to an Authorised Makita Service Centre. This guarantee does not apply where repairs have been made or attempted to be made to the machine by unauthorised persons and/or as a result of normal wear and tear, and/or of the machine has been abused or used for any purpose other than its intended specified use having regard to the capacity thereof. Nothing contained in this guarantee shall deprive the manufacturer and/or supplier on the one hand, and the consumer or customer on the other hand, of any rights or obligations they may have under and in terms of the Consumer Protection Act 68 of 2008 and any Regulations and amendments pertaining thereto from time to time ("the Act"), insofar as the Act may be applicable to the manufacture, sale and/or supply and purchase of the machine.

Please note: Manufacturer reserves the right to change specifications of parts and accessories without notice. Standard equipment and specifications of parts may vary in accordance with specifications issued in various countries.

This catalogue replaces the Makita MT Catalogue dated June 2019 edition and all previous Makita MT Catalogues. Rutherford is not responsible for printing errors (E&OE).